





**Gaskets, Inc.**  
301 W. Hwy. 16  
Rio, WI 53960-0398  
**800-558-1833**  
FAX 920-992-3124  
www.gasketsinc.com  
info@gasketsinc.com

## Product Data Sheet — GT14G


Tadpole Types: 1, 2, 3, 8, & 9




**TYPE 1**



**TYPE 2**



**TYPE 3**



**TYPE 8**

**Custom  
Design**

**TYPE 9**

<b>Description:</b>	Silicone Coated Fiberglass/Galvanized Steel tadpole seal
<b>Size:</b>	Standard and custom sizes available. See above Tadpole Types and dimensional requirements (A, B, C, & D) for standard and/or custom sizes.
<b>Cover:</b>	0.02" Thick Premium quality Silicone coated fiberglass tape. Orange-red in color.
<b>Core:</b>	Solid Mesh Galvanized Steel
<b>Temperature:</b>	500°(-150°) F/216°(-101°) C
<b>Application:</b>	Tadpole seals are used in sealing oven doors, covers, ducts, dampers, panel joints and other applications where conformance to uneven flanges is required.
<b>Chemical Resistance:</b>	Silicone rubber offers exceptional performance in adverse environments. It is reliable under many conditions that cause organic rubber to fail or deteriorate prematurely. Chemically, silicones are quite different from all other rubber like materials.
<b>Other:</b>	Has excellent mechanical properties with excellent resistance to thermal shock and vibration. It is used in a variety of applications requiring superior temperature and insulation performance.